

County of Brunswick

3954 Clearwell Dr NE
Leland, NC 28451

Northwest Plant Lab

Leland, NC
Samples Received: 02/21/2020

Analytical Report 0220-743

Isotope Dilution Method

PFAS – Legacy 24, Gen-X, PFMOAA



Enthalpy Analytical, LLC – Ultratrace

Lindsay Boone
O: (910) 212-5855 / F: 910-212-5866
lboone@enthalpy.com / www.enthalpy.com
2714 Exchange Drive, Wilmington, NC 28405

I certify that to the best of my knowledge all analytical data presented in this report:

- Have been checked for completeness
- Are accurate, error-free, and legible
- Have been conducted in accordance with approved protocol, and that all deviations and analytical problems are summarized in the appropriate narrative(s)

This analytical report was prepared in Portable Document Format (.PDF) and contains _____ pages.

Report Issued Date: _____



Summary of Results

Enthalpy Analytical

Job No.: 0220-743 PFAS by Isotope Dilution (non-potable water)

County of Brunswick N.W. Plant, Leland

Summary

	Compound	CAS	022120-S01 ng/L	022120-E01 ng/L
Acids	PFBA	375-22-4	ND U	ND U
	PFPeA	2706-90-3	ND U	ND U
	PFHxA	307-24-4	6.04	5.82
	PFHpA	375-85-9	3.82	3.49
	PFOA	335-67-1	5.87	5.76
	PFNA	375-95-1	0.752	0.784
	PFDA	335-76-2	0.517	0.521
	PFUnDA	2058-94-8	0.136 J	0.0867 J
	PFDODA	307-55-1	0.0813 J	0.0282 L
	PFTTrDA	72629-94-8	0.0841 J	ND U
	PFTeDA	376-06-7	0.167 J	ND U
Sulfonates	PFBS	375-73-5	ND U	ND U
	PFPeS	2706-91-4	ND U	ND U
	PFHxS	355-46-4	3.25	2.99
	PFHpS	375-92-8	ND U	ND U
	PFOS	1763-23-1	8.93	9.79
	PFNS	68259-12-1	ND U	ND U
	PFDS	335-77-3	ND U	ND U
	4:2 FTS	757124-72-4	ND U	ND U
	6:2 FTS	27619-97-2	0.278	0.401
Other	8:2 FTS	39108-34-4	ND U	ND U
	PFOSA	754-91-6	ND U	ND U
	N-MeFOSAA	2355-31-9	0.183 J	0.124 J
	N-EtFOSAA	2991-50-6	0.0322 L	ND U
	HFPO-DA	13252-13-6	4.85 J	4.66 J
	PFMOAA	674-13-5	2.37	2.07

QC Data

Enthalpy Analytical

Job No.: 0220-743-1 PFAS by Isotope Dilution (non-potable water)

County of Brunswick N.W. Plant, Leland

Enthalpy ID	MB-10730-PFAS	Prep Batch	EU10730	Sample Vol (mL)	250
Sample Name	MB-10730-PFAS	Prep Date	2020-02-28	Extract Vol (mL)	0.4
Matrix		Analysis Date	2020-02-28	Dilution Factor	1
Sampling Date					

	Compound	CAS	Extract Concentration ng/L	Sample Concentration ng/L	Formatted Result ng/L	LOD ng/L	LOQ ng/L	Recovery	Flags
Acids	PFBA	375-22-4	ND	ND	ND	0.157	0.240		U
	PFPeA	2706-90-3	ND	ND	ND	0.0898	0.240		U
	PFHxA	307-24-4	ND	ND	ND	0.158	0.240		U
	PFHpA	375-85-9	ND	ND	ND	0.0695	0.240		U
	PFOA	335-67-1	ND	ND	ND	0.0795	0.240		U
	PFNA	375-95-1	ND	ND	ND	0.0509	0.240		U
	PFDA	335-76-2	ND	ND	ND	0.125	0.240		U
	PFUnDA	2058-94-8	ND	ND	ND	0.0481	0.240		U
	PFDoDA	307-55-1	ND	ND	ND	0.0475	0.240		U
	PFTTrDA	72629-94-8	ND	ND	ND	0.0745	0.240		U
	PFTeDA	376-06-7	ND	ND	ND	0.0830	0.240		U
Sulfonates	PFBS	375-73-5	ND	ND	ND	0.0830	0.240		U
	PFPeS	2706-91-4	ND	ND	ND	0.0990	0.240		U
	PFHxS	355-46-4	ND	ND	ND	0.0827	0.240		U
	PFHpS	375-92-8	ND	ND	ND	0.0779	0.240		U
	PFOS	1763-23-1	ND	ND	ND	0.0471	0.240		U
	PFNS	68259-12-1	ND	ND	ND	0.0654	0.240		U
	PFDS	335-77-3	ND	ND	ND	0.135	0.240		U
	4:2 FTS	757124-72-4	ND	ND	ND	0.0646	0.240		U
	6:2 FTS	27619-97-2	ND	ND	ND	0.0723	0.240		U
	8:2 FTS	39108-34-4	ND	ND	ND	0.0569	0.240		U
Other	PFOSA	754-91-6	ND	ND	ND	0.365	0.366		U
	N-MeFOSAA	2355-31-9	ND	ND	ND	0.0544	0.240		U
	N-EtFOSAA	2991-50-6	ND	ND	ND	0.0651	0.240		U
	HFPO-DA	13252-13-6	ND	ND	ND	3.33	8.40		U
	PFMOAA	674-13-5	ND	ND	ND	0.500	2.00		U
ES	MPFBA		4901.14	7.84				67.3%	
	M5PFPeA		6348.26	10.2				85.6%	
	M3PFBS		5986.86	9.58				81.7%	
	M2-4:2 FTS		4540.18	7.26				64.8%	
	M5PFHxA		4588.50	7.34				86.0%	
	M3HFPO-DA		5515.12	8.82				101.3%	
	M4PFHpA		4841.69	7.75				92.6%	
	M3PFHxS		4452.85	7.12				69.9%	
	M2-6:2 FTS		5010.52	8.02				70.1%	
	M8PFOA		4835.37	7.74				91.6%	
	M9PFNA		4779.59	7.65				92.3%	
	M8PFOS		4878.32	7.81				80.7%	
	M2-8:2 FTS		5588.04	8.94				94.5%	
	M8FOSA-I		4180.20	6.69				65.5%	
	M6PFDA		4603.64	7.37				95.4%	
	d3-N-MeFOSAA		6348.67	10.2				100.6%	
	d5-N-EtFOSAA		7290.61	11.7				120.0%	
	M7PFUdA		5511.77	8.82				118.4%	
	MPFDoA		5698.62	9.12				124.7%	
	M2PFTeDA		4648.95	7.44				99.9%	

Narrative Summary

Enthalpy Analytical Narrative Summary

Company	County of Brunswick
Job No.	0220-743 PFAS by Isotope Dilution (non-potable water)
Client ID.	Site: N.W. Plant, Leland

1. Custody

Ian Brooker received the samples on 2/21/20 at 1.4 °C after being relinquished by County of Brunswick. The samples were received in good condition.

Prior to, during, and after analysis, the samples were kept under lock with access only to authorized personnel by Enthalpy Analytical, LLC.

Table 1 - Sample Inventory

EU Lab Sample ID	Client Sample ID	Matrix
0220-743-001-2	022120-S01	Aqueous
0220-743-002-2	022120-E01	Aqueous

2. Methods and analytes

A list of analytes of interest and corresponding methods of analysis is shown in Table 3. Abbreviations are defined in the listed Appendices. The following methods were used for sample preparation:

Table 3 - Methods and Analytes

EU Method	Analytes	Cleanup Method
EU047	Legacy 24 + Gen-X + PFMOAA	Envi-Carb

3. Analysis

The samples were analyzed for PFAS (Legacy 24 + GenX + PFMOAA) using Waters Acquity UPLC equipped with Xevo TQ MS (LC/MS/MS "Kili").

For nonaqueous samples, the sample volume was measured gravimetrically by the laboratory, and spiked with Extraction Standard (ES). The sample was then mixed well and centrifuged.

Cleanup procedures were performed on the supernatant and then extracted via SPE. Each final sample extract was transferred to an autosampler vial and spiked with 400 µL of Injection Standard (IS), prior to analysis.



Enthalpy Analytical Narrative Summary

Company	County of Brunswick
Job No.	0220-743 PFAS by Isotope Dilution (non-potable water)
Client ID.	Site: N.W. Plant, Leland

4. Calibration

In the initial calibration, the analytes met the R^2 coefficient correlation. The continuing calibration (concal) and Internal Calibration Verification (ICV) met the 30% criterion for native analytes.

5. QC Notes

QC sample analyses passed all method criteria.

The samples were extracted within the 14-day from collection holding time and analyzed within the 28-day from extraction to analysis holding time required by the method.

6. Reporting Notes

Some labeled standards in the samples fell outside the limits for ES recoveries. The target analytes are quantified based on their ratio to the labeled standards, therefore, undergo the same losses as the labeled standards. As a result, low or high recoveries do not cause any change to ratios or contribute any additional error in the measurement of the target analytes. Therefore, the data are considered acceptable.

The results presented in this report are representative of the samples as provided to the laboratory.

These analyses met the requirements of the TNI Standard. Any deviations from the requirements of the reference method or TNI Standard have been stated above.

Enthalpy Analytical, LLC in Wilmington NC is accredited by the Louisiana Department of Environmental Quality to the 2009 TNI Standard under certificate number 05075.



General Reporting Notes – Data Qualifiers

The following are general reporting notes that are applicable to all Enthalpy Analytical, LLC - Wilmington, NC data reports, unless specifically noted otherwise.

General Data Qualifiers

- B – The analyte was found in the method blank, at a concentration that was at least 10% of the concentration in the sample.
- Cxx – Two or more congeners co-elute. In EDDs, C denotes the lowest IUPAC congener in a co-elution group and additional co-eluters for the group ('xx') are shown with the number of the lowest IUPAC co-eluter.
- E – The reported concentration exceeds the calibration range (upper point of the calibration curve). For HRMS data, this condition does not imply additional measurement uncertainty. For LC-MS/MS data, these values should be considered as having measurement uncertainty higher than values within the calibration range.
- EDL – Estimated Detection Level. Specific to Dioxin/Furan tests and equivalent to MDL
- EMPC – Estimated Maximum Possible Concentration Specific to Dioxin/Furan tests to indicate the signal/noise ratio was not sufficient for peak identification (the determined ion-abundance ratio was outside the allowed theoretical range), or where there was a co-eluting interference. Indicates that a peak was identified but did not meet the method specified ion-abundance ratio.
- IR – The ion ratio between the primary and secondary ions was observed to be outside the method criteria therefore the actual analyte concentration cannot be accurately determined as defined by DoD QSM Table B-15.
- J – The analyte has a concentration below the minimum calibration level (LOQ value) but greater than the LOD. These values should be considered as having measurement uncertainty higher than values within the calibration range
- L - Indicates that an analyte has a concentration below the Minimum Detection Limit (MDL). The reported concentration is not recommended for regulatory use as the analyte signal may have a signal-to-noise ratio less than the criteria deemed necessary to be considered a detected analyte.
- LOD – Limit of Detection: For reports conforming to the DOD ELAP QSM, this is the QSM-defined LOD. For reports conforming to TNI requirements (but not DOD ELAP QSM requirements), this value is the minimum detection limit (MDL). The LOD is adjusted for sample weight or volume.
- LOQ – Limit of Quantiation: For reports conforming to the DOD ELAP QSM, this is the QSM-defined LOQ. For reports conforming to TNI requirements (but not DOD ELAP QSM requirements), this value is the reporting limit (RL). The LOD is adjusted for sample weight or volume.
- <LOD() – Analyte was not found at a concentration high enough to be reported as detected. It is reported as less than the LOD, and the LOD is given in the parentheses.

General Reporting Notes – Data Qualifiers

- ND – Indicates a non-detect.
- NR – Indicates a value that is not reportable due to issues observed in sample preparation or analysis.
- PR – The associated congener(s) is(are) poorly resolved.
- QI – Indicates the presence of a quantitative interference.
- RL – Reporting Limit. Lowest reportable value. The level is higher than the MDL.
- SI – Denotes “Single Ion Mode” and is utilized for PCBs where the secondary ion trace has a significantly elevated noise level due to background PFK. Responses for such peaks are calculated using an EMPC approach based solely on the primary ion area(s) and may be considered estimates.
- U – The analyte was not detected.
- V – The labeled standard recovery is not within method control limits.
- X – Results from re-injection/repeat/second-column analysis.


Lab Identifiers/ Data Attributes

- AR – Indicates use of the archived portion of the sample extract.
- CU – Indicates a sample that required additional clean-up prior to HRMS injection/processing.
- D – Dilution Data. Result was obtained from the analysis of a dilution. The number that follows the “D” indicates the dilution factor.
- DE – Indicates a dilution performed with the addition of ES (Extraction Standard) solution.
- DUP – Designation for a duplicate sample.
- MS – Designation for a matrix spike.
- MSD – Designation for a matrix spike duplicate.
- RJ – Indicates a reinjection of the sample extract.
- S – Indicates a sample split. The number that follows the “S” indicates the split factor.
- R – Indicates a re-extraction of the sample.

PFAS Compound Acronym List	
Acronym	Compound Name
Target Analytes	
PFBA	Perfluorobutanoic Acid
PFPeA	Perfluoropentanoic Acid
PFHxA	Perfluorohexanoic Acid
PFHpA	Perfluoroheptanoic Acid
PFOA	Perfluorooctanoic Acid
PFNA	Perfluorononanoic Acid
PFDA	Perfluorodecanoic acid
PFUnA (PFUnDA)	Perfluoroundecanoic acid
PFDoA (PFDoDA)	Perfluorododecanoic acid
PFTriDA (PFTriA)	Perfluorotridecanoic acid
PFTeDA (PFTA)	Perfluorotetradecanoic acid
PFBS	Perfluorobutane sulfonic acid
PFPeS	Perfluoropentane sulfonic acid
PFHxS	Perfluorohexane sulfonic acid
PFHpS	Perfluoroheptane sulfonic acid
PFOS	Perfluorooctane sulfonic acid
PFNS	Perfluorononane sulfonic acid
PFDS	Perfluorodecane sulfonic acid
4:2 FTS	4:2 fluorotelomer sulfonic acid
6:2 FTS	6:2 fluorotelomer sulfonic acid
8:2 FTS	8:2 fluorotelomer sulfonic acid
PFOSA (FOSA)	Perfluorooctane sulfonamide
N-MeFOSAA	N-methyl perfluorooctane sulfonamido acetic acid
N-EtFOSAA	N-ethyl perfluorooctane sulfonamido acetic acid
HFPO-DA	2,3,3,3-Tetrafluoro-2-(1,1,2,2,3,3,3-heptafluoropropoxy)-propanoic acid (Gen-X)
Extraction Standards	
MPFBA	Perfluoro-n-[13C4]butanoic acid
M5PFPeA	Perfluoro-n-[13C5]pentanoic acid
M3PFBS	Sodium perfluoro-1-[2,3,4-13C3]-butanesulfonic acid
M2-4:2 FTS	Sodium 1H,1H,2H,2H-perfluoro-1-[1,2-13C2]-hexane sulfonic acid
M5PFHxA	Perfluoro-n-[1,2,3,4,6-13C5]hexanoic acid
M3HFPO-DA	2,3,3,3-Tetrafluoro-2-(1,1,2,2,3,3,3-heptafluoropropoxy)-13C3-propanoic acid
M4PFHpA	Perfluoro-n-[1,2,3,4-13C4]heptanoic acid
M3PFHxS	Sodium perfluoro-1-[1,2,3-13C3]-hexanesulfonic acid
M2-6:2 FTS	Sodium 1H,1H,2H,2H-perfluoro-1-[1,2-13C2]-octane sulfonic acid
M8PFOA	Perfluoro-n-[13C8]octanoic acid
M9PFNA	Perfluoro-n-[13C9]nonanoic acid
M8PFOS	Sodium perfluoro-1-[13C8]-octanesulfonic acid
M2-8:2 FTS	Sodium 1H,1H,2H,2H-perfluoro-1-[1,2-13C2]-decane sulfonic acid
M8FOSA	Perfluoro-1-[13C8]octanesulfonamide
M6PFDA	Perfluoro-n-[1,2,3,4,5,6-13C6]decanoic acid
d3-N-MeFOSAA	N-methyl-d3-perfluoro-1-octanesulfonamide
d5-N-EtFOSAA	N-ethyl-d5-perfluoro-1-octanesulfonamide
M7PFUnDA (M7PFUdA)	Perfluoro-n-[1,2,3,4,5,6,7-13C7]undecanoic acid
MPFDoA	Perfluoro-n-[1,2-13C2]dodecanoic acid
M2PFTeDA	Perfluoro-n-[1,2-13C2]tetradecanoic acid

Injection Standards	
M3PFBA	Perfluoro-n-[2,3,4- ¹³ C ₃]butanoic acid
M2PFOA	Perfluoro-n-[1,2- ¹³ C ₂]octanoic acid
MPFDA	Perfluoro-n-[1,2- ¹³ C ₂]decanoic acid
MPFOS	Sodium perfluoro-1-[1,2,3,4- ¹³ C ₄]-octanesulfonic acid

Sample Custody



Enthalpy Ultratrace Job#: _____ COC Page _____ of _____

Enthalpy Analytical-Wilmington, NC has added enhancements to standard methods to improve accuracy, precision and permit an assessment of laboratory performance in the context of your specific data needs. For more information email Cindy.James@enthalpy.com.

This Chain of Custody is applicable to Non-Air samples. Standard TAT differ per analysis and are provided by request.

Report To: SAME

Location: LELAND

Email: _____

Client Special Instructions:

Matrix: GW-Groundwater, WW-Wastewater, NW-Non-Potable Water, DW-Drinking Water, S-Soil, SL-Sludge, BT-Biological Tissue, O-Other

Type: G=Grab C=Composite Q=Quality Control

[illegible]

Notes:

Relinquished By:

Date: _____

Received By:

Date:

Time:

Sample Temperature Upon Receipt:

☒ Iced ☐ Ambient °C 14°C☐ Iced ☐ Ambient °C☐ Iced ☐ Ambient °C

2714 Exchange Drive • Wilmington, NC 28405 • (910) 212-5858 • www.enthalpy.com

Samples Received from Courier, in good condition, in a cooler, on ice, no seals present, at 1.4°C using thermometer T9

JDY 2-21-20

**This Is The Last Page
Of This Report.**