

County of Brunswick

3954 Clearwell Dr NE
Leland, NC 28451

NW Lab

Leland, NC

Samples Received: 06/12/2020

Analytical Report
0620-736

Isotope Dilution Method

PFAS



Enthalpy Analytical, LLC – Ultratrace

Lindsay Boone

O: (910) 212-5855 / F: 910-212-5866

lboone@enthalpy.com / www.enthalpy.com

2714 Exchange Drive, Wilmington, NC 28405

I certify that to the best of my knowledge all analytical data presented in this report:

- Have been checked for completeness
- Are accurate, error-free, and legible
- Have been conducted in accordance with approved protocol, and that all deviations and analytical problems are summarized in the appropriate narrative(s)

This analytical report was prepared in Portable Document Format (.PDF) and contains _____ pages.

Report Issued Date: _____



Summary of Results

Enthalpy Analytical

Job No.: 0620-736 PFAS by Isotope Dilution (non-potable water)

County of Brunswick Site: NW Lab

Summary

	Compound	CAS	061220-S01 ng/L	061220-E01 ng/L
Acids	PFBA	375-22-4	ND U	ND U
	PFPeA	2706-90-3	7.21	7.55
	PFHxA	307-24-4	7.85	7.96
	PFHpA	375-85-9	4.58	4.66
	PFOA	335-67-1	6.10	5.79
	PFNA	375-95-1	0.933	0.921
	PFDA	335-76-2	0.614	0.431
	PFUnDA	2058-94-8	0.127 J	0.0821 J
	PFDoDA	307-55-1	ND U	ND U
	PFTTrDA	72629-94-8	ND U	ND U
	PFTeDA	376-06-7	ND U	ND U
Sulfonates	PFBS	375-73-5	ND U	ND U
	PFPeS	2706-91-4	0.692	0.670
	PFHxS	355-46-4	3.12	3.01
	PFHpS	375-92-8	ND U	ND U
	PFOS	1763-23-1	11.1	10.2
	PFNS	68259-12-1	ND U	ND U
	PFDS	335-77-3	ND U	ND U
	4:2 FTS	757124-72-4	ND U	ND U
	6:2 FTS	27619-97-2	0.0574 L	0.152 J
	8:2 FTS	39108-34-4	ND U	ND U
Other	PFOSA	754-91-6	ND U	ND U
	N-MeFOSAA	2355-31-9	ND U	ND U
	N-EtFOSAA	2991-50-6	ND U	ND U
	HFPO-DA	13252-13-6	4.72	3.98
	PFMOAA	674-13-5	17.9	16.5
	PFMOPrA	377-73-1	ND U	ND U
	PFO2HxA	39492-88-1	5.57	6.98
	PFO3OA	39492-89-2	6.77	5.70
	PFO4DA	39492-90-5	ND U	ND U
	Nafion Byproduct 1	29311-67-9	ND U	0.0378
	ADONA	919005-14-4	ND U	ND U
	9Cl-PF3ONS	756426-58-1	ND U	ND U
	11Cl-PF3OUdS	763051-92-9	ND U	ND U
	Nafion Byproduct 2	749836-20-2	0.737	ND U
	NFDHA	151772-58-6	ND U	ND U
	PEPA		ND U	ND U
	PFEESA	113507-82-7	ND U	ND U
	PFMOBA	863090-89-5	ND U	ND U
	PFO5DA	39492-91-6	ND U	ND U
	PMPA	13140-29-9	1.43	2.12

QC Data

Enthalpy Analytical

Job No.: 0620-736 PFAS by Isotope Dilution (non-potable water)

County of Brunswick Site: NW Lab

Enthalpy ID	MB2-10945-PFAS	Prep Batch	EU10945	Sample Vol (mL)	250
Sample Name	MB2-10945-PFAS	Prep Date	2020-06-13	Extract Vol (mL)	0.4
Matrix		Analysis Date	2020-06-13	Dilution Factor	1
Sampling Date					

	Compound	CAS	Extract Concentration ng/L	Sample Concentration ng/L	Formatted Result ng/L	LOD ng/L	LOQ ng/L	Recovery	Flags
Acids	PFBA	375-22-4	ND	ND	ND	0.157	0.240		U
	PFPeA	2706-90-3	ND	ND	ND	0.0898	0.240		U
	PFHxA	307-24-4	105.55	0.169	0.169	0.158	0.240		J
	PFHpA	375-85-9	ND	ND	ND	0.0695	0.240		U
	PFOA	335-67-1	ND	ND	ND	0.0795	0.240		U
	PFNA	375-95-1	ND	ND	ND	0.0509	0.240		U
	PFDA	335-76-2	ND	ND	ND	0.125	0.240		U
	PFUnDA	2058-94-8	ND	ND	ND	0.0481	0.240		U
	PFDoDA	307-55-1	ND	ND	ND	0.0475	0.240		U
	PFTTrDA	72629-94-8	ND	ND	ND	0.0745	0.240		U
	PFTeDA	376-06-7	ND	ND	ND	0.0830	0.240		U
Sulfonates	PFBS	375-73-5	ND	ND	ND	0.0830	0.240		U
	PFPeS	2706-91-4	ND	ND	ND	0.0990	0.240		U
	PFHxS	355-46-4	ND	ND	ND	0.0827	0.240		U
	PFHpS	375-92-8	ND	ND	ND	0.0779	0.240		U
	PFOS	1763-23-1	ND	ND	ND	0.0471	0.240		U
	PFNS	68259-12-1	ND	ND	ND	0.0654	0.240		U
	PFDS	335-77-3	ND	ND	ND	0.135	0.240		U
	4:2 FTS	757124-72-4	ND	ND	ND	0.0646	0.240		U
	6:2 FTS	27619-97-2	ND	ND	ND	0.0723	0.240		U
	8:2 FTS	39108-34-4	ND	ND	ND	0.0569	0.240		U
Other	PFOSA	754-91-6	ND	ND	ND	0.365	0.366		U
	N-MeFOSAA	2355-31-9	ND	ND	ND	0.0544	0.240		U
	N-EtFOSAA	2991-50-6	ND	ND	ND	0.0651	0.240		U
	HFPO-DA	13252-13-6	ND	ND	ND	0.0951	0.240		U
	PFMOAA	674-13-5	ND	ND	ND	0.500	2.00		U
	PFMOPrA	377-73-1	ND	ND	ND				U
	PFO2HxA	39492-88-1	ND	ND	ND				U
	PFO3OA	39492-89-2	ND	ND	ND				U
	PFO4DA	39492-90-5	ND	ND	ND				U
	Nafion Byproduct 1	29311-67-9	ND	ND	ND				U
	ADONA	919005-14-4	ND	ND	ND	0.120	0.240		U
	9Cl-PF3ONS	756426-58-1	ND	ND	ND	0.120	0.240		U
	11Cl-PF3OUdS	763051-92-9	ND	ND	ND	0.120	0.240		U
	Nafion Byproduct 2	749836-20-2	ND	ND	ND				U
	NFDHA	151772-58-6	ND	ND	ND				U
	PEPA		ND	ND	ND				U
	PFEESA	113507-82-7	ND	ND	ND				U
	PFMOBA	863090-89-5	ND	ND	ND				U
	PFO5DA	39492-91-6	ND	ND	ND				U
	PMPA	13140-29-9	ND	ND	ND				U

Enthalpy Analytical

Job No.: 0620-736 PFAS by Isotope Dilution (non-potable water)

County of Brunswick Site: NW Lab

ES	MPFBA		5142.05	8.23				101.0%	
	M5PFPeA		5211.14	8.34				100.6%	
	M3PFBS		5113.62	8.18				102.5%	
	M2-4:2 FTS		4850.42	7.76				109.5%	
	M5PFHxA		5149.66	8.24				98.3%	
	M3HFPO-DA		5197.47	8.32				100.3%	
	M4PFHpA		5216.06	8.35				99.6%	
	M3PFHxS		5058.17	8.09				92.5%	
	M2-6:2 FTS		6215.62	9.94				117.9%	
	M8PFOA		5140.71	8.23				97.1%	
	M9PFNA		5001.76	8.00				96.8%	
	M8PFOS		5173.53	8.28				95.4%	
	M2-8:2 FTS		5235.39	8.38				111.7%	
	M8FOSA-I		4179.91	6.69				82.8%	
	M6PFDA		5124.22	8.20				97.1%	
	d3-N-MeFOSAA		4681.15	7.49				89.7%	
	d5-N-EtFOSAA		4751.61	7.60				91.1%	
	M7PFUdA		4341.61	6.95				83.7%	
	MPFDoA		4053.45	6.49				82.4%	
	M2PFTeDA		2901.60	4.64				54.5%	

Narrative Summary

Enthalpy Analytical Narrative Summary

Company	County of Brunswick
Job No.	0620-736 PFAS by Isotope Dilution (non-potable water)
Client ID.	Site: NW Lab

1. Custody

Naomi Harka received the samples on 06/12/20 at 2.6°C after being relinquished by County of Brunswick. The samples were received in good condition.

Prior to, during, and after analysis, the samples were kept under lock with access only to authorized personnel by Enthalpy Analytical, LLC.

Table 1 - Sample Inventory

EU Lab Sample ID	Client Sample ID	Matrix
0620-736-001-1	061220-S01	Aqueous
0620-736-002-1	061220-E01	Aqueous

2. Methods and analytes

A list of analytes of interest and corresponding methods of analysis is shown in Table 3. Abbreviations are defined in the listed Appendices.

Table 3 - Methods and Analytes

EU Method	Analytes	Cleanup Method
EU-047	PFAS	ENVI-Carb

3. Analysis

The samples were analyzed using Waters Acquity UPLC equipped with Xevo TQ MS (LC/MS/MS "Kili").

For aqueous samples, the sample volume was measured gravimetrically by the laboratory, and spiked with Extraction Standard (ES). The sample was then mixed well and centrifuged.

Cleanup procedures were performed on the supernatant and then extracted via SPE. Each final sample extract was transferred to an autosampler vial and spiked with 80µL of Injection Standard (IS), prior to analysis.



Enthalpy Analytical Narrative Summary

Company	County of Brunswick
Job No.	0620-736 PFAS by Isotope Dilution (non-potable water)
Client ID.	Site: NW Lab

4. Calibration

In the initial calibration, the analytes exhibited R^2 of ≥ 0.99 . The calibration standard analytes, continuing calibration (concal) and Initial Calibration Verification (ICV) met the 30% criterion for native analytes.

5. QC Notes

QC sample analyses passed all method criteria.

The following analyte(s) was detected in the method blank (MB) below the Reporting Limit (RL) with values less than 1/10 the sample amount, therefore meeting method criteria.

MB-10945-PFAS PFHxA

The samples were extracted within the 28-day from collection holding time and analyzed within the 28-day from extraction to analysis holding time required by the method.

6. Reporting Notes

Some labeled standards in the samples fell outside the limits for ES recoveries. The target analytes are quantified based on their ratio to the labeled standards, therefore, undergo the same losses as the labeled standards. As a result, low or high recoveries do not cause any change to ratios or contribute any additional error in the measurement of the target analytes. Therefore, the data are considered acceptable.

The results presented in this report are representative of the samples as provided to the laboratory.

These analyses met the requirements of the TNI Standard. Analytes reported in addition to Legacy 24 analytes are currently not accredited under the TNI standard as noted on the PFAS Compound Acronym List. Any deviations from the requirements of the reference method or TNI Standard have been stated above.

Enthalpy Analytical, LLC in Wilmington NC is accredited by the Louisiana Department of Environmental Quality to the 2009 TNI Standard under certificate number 05075.





General Reporting Notes – Data Qualifiers

The following are general reporting notes that are applicable to all Enthalpy Analytical, LLC - Wilmington, NC data reports, unless specifically noted otherwise.

General Data Qualifiers

- B – The analyte was found in the method blank, at a concentration that was at least 10% of the concentration in the sample.
- Cxx – Two or more congeners co-elute. In EDDs, C denotes the lowest IUPAC congener in a co-elution group and additional co-eluters for the group ('xx') are shown with the number of the lowest IUPAC co-eluter.
- E – The reported concentration exceeds the calibration range (upper point of the calibration curve). For HRMS data, this condition does not imply additional measurement uncertainty. For LC-MS/MS data, these values should be considered as having measurement uncertainty higher than values within the calibration range.
- EDL – Estimated Detection Level. Specific to Dioxin/Furan tests and equivalent to MDL
- EMPC – Estimated Maximum Possible Concentration Specific to Dioxin/Furan tests to indicate the signal/noise ratio was not sufficient for peak identification (the determined ion-abundance ratio was outside the allowed theoretical range), or where there was a co-eluting interference. Indicates that a peak was identified but did not meet the method specified ion-abundance ratio.
- IR – The ion ratio between the primary and secondary ions was observed to be outside the method criteria therefore the actual analyte concentration cannot be accurately determined as defined by DoD QSM Table B-15.
- J – The analyte has a concentration below the minimum calibration level (LOQ value) but greater than the LOD. These values should be considered as having measurement uncertainty higher than values within the calibration range
- L - Indicates that an analyte has a concentration below the Minimum Detection Limit (MDL). The reported concentration is not recommended for regulatory use as the analyte signal may have a signal-to-noise ratio less than the criteria deemed necessary to be considered a detected analyte.
- LOD – Limit of Detection: For reports conforming to the DOD ELAP QSM, this is the QSM-defined LOD. For reports conforming to TNI requirements (but not DOD ELAP QSM requirements), this value is the minimum detection limit (MDL). The LOD is adjusted for sample weight or volume.
- LOQ – Limit of Quantitation: For reports conforming to the DOD ELAP QSM, this is the QSM-defined LOQ. For reports conforming to TNI requirements (but not DOD ELAP QSM requirements), this value is the reporting limit (RL). The LOD is adjusted for sample weight or volume.
- <LOD() – Analyte was not found at a concentration high enough to be reported as detected. It is reported as less than the LOD, and the LOD is given in the parentheses.

General Reporting Notes – Data Qualifiers

- ND – Indicates a non-detect.
- NR – Indicates a value that is not reportable due to issues observed in sample preparation or analysis.
- PR – The associated congener(s) is(are) poorly resolved.
- QI – Indicates the presence of a quantitative interference.
- RL – Reporting Limit. Lowest reportable value. The level is higher than the MDL.
- SI – Denotes “Single Ion Mode” and is utilized for PCBs where the secondary ion trace has a significantly elevated noise level due to background PFK. Responses for such peaks are calculated using an EMPC approach based solely on the primary ion area(s) and may be considered estimates.
- U – The analyte was not detected.
- V – The labeled standard recovery is not within method control limits.
- X – Results from re-injection/repeat/second-column analysis.

Lab Identifiers/ Data Attributes

- AR – Indicates use of the archived portion of the sample extract.
- CU – Indicates a sample that required additional clean-up prior to HRMS injection/processing.
- D – Dilution Data. Result was obtained from the analysis of a dilution. The number that follows the “D” indicates the dilution factor.
- DE – Indicates a dilution performed with the addition of ES (Extraction Standard) solution.
- DUP – Designation for a duplicate sample.
- MS – Designation for a matrix spike.
- MSD – Designation for a matrix spike duplicate.
- RJ – Indicates a reinjection of the sample extract.
- S – Indicates a sample split. The number that follows the “S” indicates the split factor.
- R – Indicates a re-extraction of the sample.

Brunswick County PFAS Analyte List

	PFAS Analyte	CAS #
*	Perfluoro(2-ethoxyethane)sulphonic acid (PFEESA)	113507-82-7
*	Hexafluoropropylene Oxide Dimer Acid (HFPOA-DA/Gen X)	13252-13-6(b)
*	Nonafluoro-3,6-dioxaheptanoic acid (NFDHA)	151772-58-6
	Perfluorooctanesulfonate (PFOS)	1763-23-1
	Perfluoroundecanoic acid (PFUdA)	2058-94-8
	N-methylperfluoro-1-octanesulfonamidoacetic acid (N-MeFOSAA)	2355-31-9
	Perfluoropentanoic acid (PFPeA)	2706-90-3
	Perfluoropentanesulfonate (PFPeS)	2706-91-4
	Fluorotelomer sulfonate 6:2 (6:2 FTS)	27619-97-2
	Perfluorodecanesulfonate (PFDS)	2806-15-7
	Nafion Byproduct 1	29311-67-9
	N-ethylperfluoro-1-octanesulfonamidoacetic acid (N-EtFOSAA)	2991-50-6
	Perfluorohexanoic acid (PFHxA)	307-24-4
	Perfluorododecanoic acid (PFDoA)	307-55-1
	Perfluorooctanoic acid (PFOA)	335-67-1
	Perfluorodecanoic acid (PFDA)	335-76-2
	Perfluorohexanesulfonate (PFHxS)	355-46-4
	Perfluorobutyric acid (PFBA)	375-22-4
	Perfluorobutanesulfonate (PFBS)	375-73-5
	Perfluoroheptanoic acid (PFHpA)	375-85-9
	Perfluoroheptanesulfonate (PFHpS)	375-92-8
	Perfluorononanoic acid (PFNA)	375-95-1
	Perfluorotetradecanoic acid (PFTeDA)	376-06-7
*	Perfluoro-3-methoxypropanoic acid (PFMOPrA)	377-73-1
	Fluorotelomer sulfonate 8:2 (8:2 FTS)	39108-34-4
*	Perfluoro(3,5-dioxahexanoic) acid (PFO2HxA)	39492-88-1
*	Perfluoro(3,5,7-trioxaoctanoic) acid (PFO3OA)	39492-89-2
*	Perfluoro(3,5,7,9-tetraoxadecanoic) acid (PFO4DA)	39492-90-5
*	Perfluoro(3,5,7,9,11-pentaoxadodecanoic) acid (PFO5DA)	39492-91-6
	Perfluorononanesulfonate (PFNS)	474511-07-4
*	Perfluoro-2-methoxyacetic acid (PFMOAA)	674-13-5
	Perfluorotridecanoic acid (PFTrDA)	72629-94-8
*	Nafion Byproduct 2	749836-20-2
	Perfluorooctanesulfonamide (PFOSA)	754-91-6
*	9-chlorohexadecafluoro-3-oxanonane-1-sulfonate (9Cl-PF3PONS)	756426-58-1 (d)
	Fluorotelomer sulfonate 4:2 (4:2 FTS)	757124-72-4
*	11-chloroeicosafluoro-3-oxaundecane-1-sulfonate (11Cl-PF3OUdS)	763051-92-9 (c)
*	Perfluoro-4-methoxybutanic acid (PFMOBA)	863090-89-5
	Sodium dodecafluoro-3H-4,8-dioxanonanoate (ADONA)	919005-14-4(e)
*	Perfluoro-2-ethoxypropanoic acid (PEPA)	N/A
*	Perfluoro-2-methoxypropanoic acid (PMPA)	13140-29-9

* Analytes are currently not accredited under TNI Standard for NPW. Accreditation pending.

Sample Custody



Enthalpy Ultratrace Job#: _____ COC Page _____ of _____

☒ Standard Turn Around Time☐ Rush Turn Around Time -- Date Needed _____

• All Fast TATs Subject to Approval by Enthalpy Analytical, Inc.

• All Samples Disposed of After 6 months Unless Otherwise Instructed.

Enthalpy Analytical-Wilmington, NC has added enhancements to standard methods to improve accuracy, precision and permit an assessment of laboratory performance in the context of your specific data needs. For more information email Cindy.James@enthalpy.com.

This Chain of Custody is applicable to Non-Air samples. Standard TAT differ per analysis and are provided by request.

Client Name: BRUNSWICK COUNTY WATER
Project Manager: GLEN WALKER
Report To: SAME

Project Number: _____
Site Name: N.W. LA13
Location: N.W. WATER WATER

PO#: _____
Phone#: _____
Email: _____

Client Special Instructions:

Matrix: GW-Groundwater, WW-Wastewater, NW-Non-Potable Water, DW-Drinking Water, S-Soil, SL-Sludge, BT-Biological Tissue, O-Other

Type: G=Grab C=Composite Q=Quality Control

[illegible]

Relinquished By:

Date: _____

Received By:

Date: _____

Time:

Sample Temperature Upon Receipt:

6-12-34

How Many

6/12/20	
---------	--

14:05

☒ Iced ☐ Ambient °C 2.6, T9☐ Iced ☐ Ambient °C☐ Iced ☐ Ambient °C

2714 Exchange Drive • Wilmington, NC 28405 • (910) 212-5858 • www.enthalpy.com

Courier, cooler, NO seal, iced, good condition NH 6/12/20 EU #0620-736 15 of 16

**This Is The Last Page
Of This Report.**